



019-8008 through 019-8011

Kernmantle Rope HLL : Chain Anchors

FEATURES :

- 2 Person HLL System
- Available in lengths from 30' to 100'
- Abrasion-resistant kernmantle rope:
 - Tensile Strength: 11,261lbs
- Secure rope tensioner
- Web energy absorber with protective cover reduces impact forces
- Convenient carry and storage bag

PERSONAL ATTACHMENT POINT(S)

- 2 O-rings
 - Minimum Breaking Strength: 5,000lbs

SYSTEM ATTACHMENT POINT(S)

- 2 Carabiners
 - Gate Rating: 3,600lbs
 - Minimum Breaking Strength: 5,000lbs
- 2 Chain Anchors
 - Minimum Breaking Strength: 5,000lbs

ITEM WEIGHT :

- Weight Varies per length



USER WEIGHT CAPACITY	
ANSI	130-310lbs (140.6kg) per person; 2 Person maximum
OSHA	420lbs (190.5kg) per person; 1 Person maximum

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)	
019-8008	30 Feet (14.4lbs)
019-8009	60 Feet (17.4lbs)
019-8010	80 Feet (19.4lbs)
019-8011	100 Feet (21.4lbs)

COMPONENT	MATERIAL SPECIFICATION
Rope	16mm Kernmantle Rope
Rope Tensioner	YCM Plated Steel
Energy Absorber	Polyester
O-rings	Clear Zinc Plated Steel
Carabiners	YCM Plated Steel
Bag	Polyester
Chain Anchors	Reinforced Synthetic Flexible Membrane; Painted Steel Chain, O-ring, Anchor Plates