



LIGHTWEIGHT, LOW-COST SOLUTIONS **NEW CONCRETE ANCHOR OPTIONS**

5K SWIVEL D-RING ANCHOR

TWO OPTIONS:

1

Assembly includes 5/8" heavy duty wedge style expansion bolt for easy install and removal.

2

Anchor only without fastener to allow choice of wedge or screw style bolt.



021-4081
Assembly

021-4082
Anchor Only

5K SWIVEL D-RING








FEATURES

- Lightweight, versatile and low cost
- Swivels with 180°/360° rotation
- Installs and removes quickly
- Temporary or permanent
- Vertical or horizontal use
- Single anchor point or with HLL system
- Reusable concrete anchor

ANSI Weight Capacity:	130-310 lbs. (59-141 kg)
OSHA Weight Capacity:	Up to 420 lbs. (191 kg)
Breaking Strength:	5,000 lbs. minimum
ANSI Standards:	Z359.18-2017 Type A
OSHA Standards:	1926.502, 1910.66

ANCHOR ASSEMBLY, ANCHOR & PARTS

	021-4081	5K Swivel D-ring Anchor Assembly
	021-4082	5K Swivel D-ring Anchor
	021-4083	5K Swivel D-ring Anchor Bushing/Washer Set
	021-4073	10K Replacement Concrete Wedge Bolt
	021-4053	Replacement Concrete Bolt

