



## 019-12041 through 019-12047 Ladder Climb System, 4-Person Complete Kit

### FEATURES :

- 4-person top bracket with energy-absorbing head unit
- 3/8" corrosion-resistant galvanized steel cable
- Pre-swaged termination for added protection
- 3,600 lb. single user anchor point
- Tension retaining base bracket adjusts to conditions
- All mounting hardware included
- Product inspection label included
- Cable sleeve and intermediate guides sold separately
- System capacity: up to 1240 lbs. (562 kg) when used with the EVO or any ANSI Z359.16 rated detachable cable sleeves

### FALL ARREST POINT(S) :

- D-ring on top bracket

### ITEM WEIGHT :

- See chart below



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	A14.3
OSHA	1926.1053, 1910.29, 1926.502, 1910.140

SIZE(S)	
019-12041	30ft (9.1m) / 25.8 lbs. (11.7 kg)
019-12043	50ft (15.2m) / 29.8 lbs. (13.5 kg)
019-12045	70ft (21.3m) / 33.8 lbs. (15.3 kg)
019-12047	90ft (27.4m) / 37.8 lbs. (17.1 kg)

COMPONENT	MATERIAL SPECIFICATION
Top Bracket	Galvanized Steel, Powder coated stainless steel
Bottom Bracket	Galvanized steel, stainless steel
Cable	3/8" Galvanized steel cable
U-Bolts/Nuts	Zinc plated steel
D-Ring	Powder coated carbon steel
Label	Stainless steel