



019-8034

Description: Bolt-on SafeLink Post Baseplate

FEATURES :

- For use with the FS-EX5501-5 aluminum post for the SafeLink HLL system.
- Mounts securely to steel or concrete structures.
- For Concrete Installation (in 3000 PSI or higher concrete):
 - Use (4) 1/2" diameter anchor rods with epoxy or
 - Use (4) 1/2" diameter concrete mechanical anchors.
- For Steel Installation:
 - Use (4) 1/2" grade 8 bolts with locking hardware.
- Base Dimensions: 12" (304.8 mm) x 12" (304.8 mm) x 3/4" (19.1 mm)
- Height: 12.8" (325.1 mm)
- Minimum Breaking Strength: 5,000 lbs. (22 kN)

ITEM WEIGHT :

- 53 lbs. (24 kg)



| USER WEIGHT CAPACITY | |
|----------------------|----------------------------|
| ANSI | 130-310 lbs. (59-140.6 kg) |
| OSHA | n/a |

| STANDARD COMPLIANT WITH | |
|-------------------------|----------|
| ANSI | n/a |
| OSHA | 1926.502 |

| SIZE(S) | |
|---------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

| COMPONENT | MATERIAL SPECIFICATION |
|-----------|------------------------|
| Anchor | Galvanized steel |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |