



022-12111 through 022-12119

Stainless Steel Ladder Climb System, Complete Kit

FEATURES :

- 2-person top bracket with energy-absorbing head unit
- 3/8" corrosion-resistant stainless steel cable
- Pre-swaged termination for added protection
- 3,600 lb. single user anchor point
- Tension retaining base bracket adjusts to conditions
- All mounting hardware included
- Product inspection label included
- Cable sleeve and intermediate guides sold separately
- System capacity: up to 620 lbs. (281.2 kg) when used with the EVO or any ANSI Z359.16 rated detachable cable sleeves

FALL ARREST POINT(S) :

- D-ring on top bracket

ITEM WEIGHT :

- See chart below



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	A14.3
OSHA	1926.1053, 1910.29, 1926.502, 1910.140

SIZE(S)	
022-12111	20 ft. (6.1 m) / 17.2 lbs. (7.8 kg)
022-12112	30 ft. (9.1 m) / 19.2 lbs. (8.7 kg)
022-12113	40 ft. (12.2 m) / 21.2 lbs. (9.6 kg)
022-12114	50 ft. (15.2 m) / 23.2 lbs. (10.5 kg)
022-12115	60 ft. (18.3 m) / 25.2 lbs. (11.4 kg)
022-12116	70 ft. (21.3 m) / 27.2 lbs. (12.3 kg)
022-12117	80 ft. (24.4 m) / 29.2 lbs. (13.2 kg)
022-12118	90 ft. (27.4 m) / 31.2 lbs. (14.2 kg)
022-12119	100 ft. (30.5 m) / 33.2 lbs. (15.1 kg)

COMPONENT	MATERIAL SPECIFICATION
Top Bracket	Stainless steel, Powder coated stainless steel
Bottom Bracket	Stainless steel
Cable	3/8" Stainless steel cable
U-Bolts/Nuts	Stainless steel
D-ring	Powder coated stainless steel
Label	Stainless steel