



## 022-12136 through 022-12144 Stainless Steel Cable Assembly

### FEATURES :

- 3/8" corrosion-resistant stainless steel cable
- Stainless steel thimble to protect cable eye
- Pre-swaged termination for added protection
- Custom lengths also available by request

### FALL ARREST POINT(S) :

- N/A

### ITEM WEIGHT :

- See chart below



USER WEIGHT CAPACITY	
ANSI	N/A
OSHA	N/A

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	N/A

SIZE(S)	
022-12136	20 ft. (6.1 m) / 4 lbs. (1.8 kg)
022-12137	30 ft. (9.1 m) / 6 lbs. (2.7 kg)
022-12138	40 ft. (12.2 m) / 8 lbs. (3.6 kg)
022-12139	50 ft. (15.2 m) / 10 lbs. (4.5 kg)
022-12140	60 ft. (18.3 m) / 12 lbs. (5.4 kg)
022-12141	70 ft. (21.3 m) / 14 lbs. (6.3 kg)
022-12142	80 ft. (24.4 m) / 16 lbs. (7.2 kg)
022-12143	90 ft. (27.4 m) / 18 lbs. (8.2 kg)
022-12144	100 ft. (30.5 m) / 20 lbs. (9.1 kg)

COMPONENT	MATERIAL SPECIFICATION
Cable	3/8" Stainless steel cable
Thimble	Stainless steel
Ferrules	Aluminum