



022-4084

Description: SRL Swivel Roof Anchor

FEATURES :

- For use on Z-purlin, metal decking, and wood pitched or flat roof structures, or on flat 3000 PSI or higher concrete surfaces.
- 360° swivel base
- Accommodates most SRL sizes
- Anchor post for SRL quick attachment
- D-ring connection point for EA lanyards, VLLs and HLLs
- Temporary and reusable
- (8) Lag screws for wood and (16) self-tapping screws for metal included.
- For installation on concrete, use (8) 1/4" x 1-3/4" hex head Tapcon fasteners (not included)
- Minimum Breaking Strength: 5,000 lbs.

FALL ARREST POINT(S) :

- D-ring for energy absorbing lanyards, VLLs, and HLLs
- Anchor post for SRLs

ITEM WEIGHT :

- 18.2 lbs (8.3 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1910.140, 1926.502, 1910.66

SIZE(S)	
N/A	

COMPONENT	MATERIAL SPECIFICATION
Anchor Base	Powder coated steel
Anchor Cradle	Powder coated steel
D-ring	Powder coated steel
Anchor Post	Stainless steel
Bolts/caps	Stainless steel
Fasteners	Steel