



022-4085

Description: Removable Concrete Anchor

FEATURES :

- Removable and reusable
- 360° Rotating connection point
- Easy trigger provides quick release
- Durable cap for hammer assisted removal
- Stainless steel construction for better corrosion resistance
- Protective label cover
- For horizontal, vertical and overhead use.
- Requires 3/4" diameter x 3" depth drilled hole for installation
- Anchor clearance: 6" diameter
- Minimum Breaking Strength (when installed in reinforced concrete):
 - 5,000 lbs. in 3,000 PSI concrete
 - 10,000 lbs. in 4,000 PSI or higher concrete
- Working Load Limit:
 - 1,800 lbs. in 4,000 PSI or higher concrete

FALL ARREST POINT(S) :

- D-ring

ITEM WEIGHT :

- 0.9 lbs (0.4 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	Up to 420 lbs. (191 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.18-2017 Type T
OSHA	1926.502, 1910.140, 1910.66

SIZE(S)	
N/A	

COMPONENT	MATERIAL SPECIFICATION
Anchor Body	Stainless steel
D-ring	Stainless steel
Cap	Plated steel
Trigger	Nylon
Label Cover	Polyester