



## 022-4090

### Membrane Anchor

#### FEATURES :

- Permanent single point anchor designed for membrane roofs
- Easy drop-through installation does not require access to underside of roof
- Elevated (4") anchor point keeps connecting hardware off the roof surface, preventing wear and tear
- 360° working radius
- Accommodates roof thicknesses from 3" to 12"
- Ideal for use as single point anchor or with VLL systems. Not for HLL use.

#### MINIMUM BREAKING STRENGTH (MBS) :

- 3,600 lbs. (16 kN)

#### FALL ARREST POINT(S) :

- 1 Eye-bolt

#### BASE PLATE DIMENSIONS :

- 11.6" x 11.6" (295 mm x 295 mm)

#### ITEM WEIGHT :

- 6.2 lbs. (2.8 kg)



AFTER INSTALLATION, SEE MANUAL FOR DETAILS



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	N/A

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1910.140, 1926.502, 1910.66

SIZE(S)	
N/A	

COMPONENT	MATERIAL SPECIFICATION
Toggles	Zinc plated steel, galvanized steel, stainless steel
Retro-Washer	Stainless steel
Membrane Plate	Stainless steel
Eye-bolt Assembly	Stainless steel
Tube	PVC
Insulation	Closed cell foam