



## 022-4094

### TileLink Anchor (Rivets)

#### FEATURES :

- Unique profile is designed to install under roof tiles with only the connection point exposed
- Permanent installation into metal truss
- Built-in energy absorber reduces stress or damage to the mounting structure
- Includes rivets for installation
  - (5) 8mm bulb rivets
  - Replacement rivets and hand rivet tool are available separately
- Suitable for roofs with pitch up to 7/12
- Not for use for material lifting, rappelling/rope access, or HLL systems

#### MINIMUM BREAKING STRENGTH (MBS) :

- 3,600 lbs. (16 kN)

#### FALL ARREST POINT(S) :

- 1 Formed Loop

#### ITEM WEIGHT :

- 1.6 lbs. (0.7 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-141 kg)
OSHA	N/A

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1910.140, 1926.502, 1910.66

RELATED PRODUCTS	
022-4092	TileLink Anchor (Screws)
019-4005	FrogLink Temporary Roof Anchor
019-4006	FrogLink Permanent Roof Anchor with Rivets
020-16001	Replacement Rivets
019-21001	Hand Rivet Tool

COMPONENT	MATERIAL SPECIFICATION
Anchor Plate	Stainless steel
Rivets	Aluminum