



FS871

Knock-Down Roof Anchor

FEATURES :

- Knockdown, disposable design
- Installs on pitched wood roofs
- Anchor can be shaped by hand to conform to different roof contours
- Not for permanent use, not reusable
- Not for HLL use
- Minimum breaking strength: 3,600 lbs. (16 kN)
- Size: 10" x 6" x 2.25" (25.4 x 15.2 x 5.7cm)
- Fasteners not included with FS871
- (8) 16D roofing nails are included with FS871N
- Also available in pack of 25: FS871-25

FALL ARREST POINT(S) :

- 1 formed dual layer eyelet

ITEM WEIGHT :

- 0.8 lbs. (0.4 kg)



| USER WEIGHT CAPACITY | |
|----------------------|-------------------------|
| ANSI | 130-310 lbs. (140.6 kg) |
| OSHA | N/A |

| STANDARD COMPLIANT WITH | |
|-------------------------|-----------------------------|
| ANSI | N/A |
| OSHA | 1926.502, 1910.140, 1910.66 |

| RELATED PRODUCTS | |
|------------------|-----------------------------------|
| FS871N | Knock-Down Roof Anchor, 8pc Nails |
| FS871-25 | Knock-Down Roof Anchor: Pack 25 |
| 021-4067 | 8pc 16D Roofing Nails for FS871 |
| | |
| | |
| | |
| | |
| | |

| COMPONENT | MATERIAL SPECIFICATION |
|---------------------|------------------------|
| Anchor | Zinc plated steel |
| Nails (FS871N only) | Plated steel |
| | |
| | |
| | |
| | |
| | |
| | |