



# SAFEWAZE

## SRL-P USE IN MOBILE ELEVATED WORKING PLATFORMS

### What you need to know to use the Latitude 6' Web SRL-Ps below D-ring on a MEWP

The Latitude 6' Web SRL-Ps meets OSHA compliance for fall protection on a Mobile Elevated Work Platform (MEWPs) when the user follows the Safewaze product manual, including the following guidelines:

- 1** The SRL-P may be used only when there are no sharp edges and the platform has a guardrail system with a latching gate.
- 2** The energy-absorbing portion of the SRL-P is mounted to the dorsal D-ring of the user's harness.
- 3** The MEWP anchorage for the SRL-P must meet the ANSI Z359 Fall Protection Code.

**NOTE:** For OSHA compliance, the Latitude 6' Web SRL-P can be tied off 5' below the user's D-ring. To meet ANSI standards, the Latitude 6' Web SRL-P must be tied off above the dorsal D-ring.

**QUESTIONS?  
CALL TECHNICAL SUPPORT  
800.230.0319**



### MEWP in Motion

*What about using an SRL on a moving platform?*

An SRL-P will not ensure the user is properly restrained while the MEWP is in motion and could result in the user being ejected. User should utilize a non-energy absorbing restraint lanyard connected to the side positioning D-rings when the platform is in motion.

As always, our responsive experts deliver the on-demand knowledge you need on product use, industry standards, training and more.