



# FS-EX1530-W

Northstar Classic 30' Web SRL



**Features and Benefits** Class B SRL  
High-strength polymer housing  
1" UHMPE webbing  
Steel carabiner attachment

Steel snap hook connection

**Length of Web** 30 ft (9.1 m)

**Weight of Unit** 11.3 lbs (5.1 kg)

**Hook Ratings** 5,000 lbs (2267.96 kg) Tensile Strength  
3,600 lbs (1632 kg) Gate Rated

**Maximum Arresting Force** <1,800 lbs (816.47 kg)

**Maximum Arrest Distance** <54 in (1371.6 mm)

**Standards Compliant With**

ANSI	Z359.14-14, A10.32
OSHA	1926.502

**ANSI SRL Class** Class B

**User Weight Capacity** ANSI 130-310 lbs (140.6 kg)  
OSHA Up to 420 lbs (190.5 kg)

Material Specifications:	
Webbing	1" UHMPE
Lifeline Connector	Forged Steel Snap Hook
Housing	Polymer
Housing Connector	Forged Steel Carabiner



# FS-EX1550-W

Northstar Classic 50' Web SRL



**Features and Benefits** Class B SRL  
 High-strength polymer housing  
 1" UHMPE webbing  
 Steel carabiner attachment

Steel snap hook connection

**Length of Web** 50 ft (15.2 m)

**Weight of Unit** 11.3 lbs (5.1 kg)

**Hook Ratings** 5,000 lbs (2267.96 kg) Tensile Strength  
3,600 lbs (1632 kg) Gate Rated

**Maximum Arresting Force** <1,800 lbs (816.47 kg)

**Maximum Arrest Distance** <54 in (1371.6 mm)

**Standards Compliant With**

ANSI	Z359.14-14, A10.32
OSHA	1926.502

**ANSI SRL Class** Class B

**User Weight Capacity** ANSI 130-310 lbs (140.6 kg)  
OSHA Up to 420 lbs (190.5 kg)

Material Specifications:	
Webbing	1" UHMPE
Lifeline Connector	Forged Steel Snap Hook
Housing	Polymer
Housing Connector	Forged Steel Carabiner