



023-8087

SafeLink Nelson/Rebar Assembly

FEATURES :

- Versatile base with the ability to accommodate a variety of mounting configurations including, nelson (shear) stud, L-shaped and straight rebar
- Adjustable clamps fit rebar/stud dimensions:
 - Diameter of 1/2"-1-3/8"
 - Minimum shaft height of 4"
 - Spacing from 2-1/2"-7-1/4"
- Quick and easy installation with reduced amount of hardware.
- Minimal trip hazard with 3-4' footprint.
- Durable YCM plated steel construction.
- Single or Multi-Span.
- Use with most HLL systems.
- Maximum 2 users per span.
- Sleeve for use with FS-EX5501-5 anchor post
- Max. Height: 12.75" (323.9 mm)
- Max. Width: 15.5" (393.7 mm)
- Assembly Span: 36"-48" (914.4-1219.2 mm)
- Minimum Breaking Strength: 5,000 lbs. (2268 kg)

ITEM WEIGHT :

- 53.2 lbs. (24.1 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (140.6 kg)
OSHA	N/A

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1926.502, 1910.66

COMPATIBLE COMPONENTS	
FS-EX2514	SafeLink Whizzler Cap
FS-EX10000	65' SafeLink Come-A-Long Kit
019-8016	2-Person Cable HLL System
019-8012	4-Person Rope HLL System
019-8008	2-Person Kernmantle Rope HLL System
023-8092	SafeLink Nelson Clamp Set
023-8093	SafeLink Nelson/Rebar Collared Base
023-8094	SafeLink Nelson/Rebar Support Base

COMPONENT	MATERIAL SPECIFICATION
Collared Base	YCM plated steel
Support Base	YCM plated steel
Cable	3/8" galvanized steel cable, copper ferrules
Turnbuckle	Galvanized steel
Clamps/Wingnuts	YCM plated steel