



Latitude HD 11' Cable SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Reliable internal braking system eliminates need for external shock pack.
- Durable housing increases strength and longevity.
- Rugged cable provides extreme durability.
- 360/180° attachment point offers full range of motion.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class
1
Anchor at or above dorsal D-ring

Product shown:
FS-FSP1211-G

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 33 in. (84 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	6 ft. 3 in. (1.9 m)
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 15 in. (38 cm)
Max. free fall distance	36 in. (91 cm)
Use below d-ring	3 ft. (0.91 m)
Min. required fall clearance	7 ft. 9 in. (2.4 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Cable	4.8 mm galvanized or stainless steel cable (dependent on configuration)
Housing	Polymer
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)

