



Latitude Pro 7' Web 40" Tie-Back SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Tie-back convenience when no traditional anchor is available.
- Dependable 5000 lb. rated gate, forged steel tie-back snap hook.
- Reliable internal braking system eliminates need for external shock pack.
- High strength semi-sealed assembly protects internal components from debris to extend product life.
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly.
- 360/180° attachment point offers full range of motion.
- Protective label cover for product longevity and traceability.
- 40" wear pad protected tie-back leg(s).
- Single leg and dual leg options available.
- Available with various attachment options, see chart.
- All components are Z359.12 compliant.



Product shown:
018-5034

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1910.140, 1910.66

OSHA (ABOVE & BELOW D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	*See product manual
Max. free fall distance	*See product manual
Use below d-ring	*See product manual
Min. required fall clearance	*See product manual
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Webbing	20 mm Dyneema® webbing, polyester webbing
Housing	Clear resin
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel



Latitude Pro 7' Web 40" Tie-Back SRL-P



Standards: OSHA 1910.140, 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

Part Number	Single Leg (S) / Dual Leg (D)	SRL Class	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	CONNECTOR										ATTACHMENT																						
							LI Steel Swivel Snap Hook ①	LI Steel Swivel Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	Steel Swivel Rear Hook ⑤	Steel Swivel Rear Hook ⑥	Steel Swivel Rear Hook ⑦	Steel Swivel Rear Hook ⑧	ALU Captive Eye Carabiner ⑨	ALU Captive Eye Carabiner ⑩	ALU Swivel Carabiner ⑪	No Attachment ⑫	Tip-Lock Steel Carabiner ⑬	Steel Carabiner ⑭	ALU Captive Eye Carabiner ⑮	ALU Carabiner ⑯	ALU Snap Hook ⑰	FS-ES13 ⑱	Cad Mount Bracket ⑲	Integrated B/W ⑳	Soft Loop ㉑	1014 B/W ㉒	9012 B/W ㉓	9013 B/W ㉔									
018-5028	1	S	7	Dyneema® Webbing	.7X.05	Clear Resin									X								X																
018-5029	1	S	7	Dyneema® Webbing	.7X.05	Clear Resin									X									X															
018-5030	1	S	7	Dyneema® Webbing	.7X.05	Clear Resin									X									X															
018-5031	1	S	7	Dyneema® Webbing	.7X.05	Clear Resin									X									X															
018-5032	1	D	7	Dyneema® Webbing	.7X.05	Clear Resin									X								X				X												
018-5033	1	D	7	Dyneema® Webbing	.7X.05	Clear Resin									X								X				X												
018-5034	1	D	7	Dyneema® Webbing	.7X.05	Clear Resin									X								X				X												
018-5035	1	D	7	Dyneema® Webbing	.7X.05	Clear Resin									X								X				X												
018-5036	1	D	7	Dyneema® Webbing	.7X.05	Clear Resin									X																								X
019-5136	1	D	7	Dyneema® Webbing	.7X.05	Clear Resin									X																						X		
023-5371	1	D	7	Dyneema® Webbing	.7X.05	Clear Resin									X																							X	

