



021-1714 through 021-1717

V-Select Construction Harness: 3D, QC Chest, FD, TB Legs

FEATURES:

- Dorsal D-ring
- Integrated SRL channel
- Front D-ring
- Side positioning D-rings
- Friction buckle torso adjusters
- Quick-connect chest
- Tongue buckle legs
- Breakaway lanyard keepers
- Label cover with size indicator
- Fixed shoulder pad
- Fixed waist pad

FALL ARREST POINT(S):

- 1 Dorsal D-ring
- 1 Dorsal SRL channel

ITEM WEIGHT:

- 6.2 lbs. (2.8 kg)



DORSAL
ATTACHMENT



STERNAL
ATTACHMENT



WAIST
ATTACHMENT

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

SIZE(S)	
021-1714	X-Small / Small
021-1715	Medium / Large
021-1716	X-Large / 2X
021-1717	3X

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

COMPONENT	MATERIAL SPECIFICATION
Webbing	Polyester
D-ring(s)	Stamped zinc plated steel with EP coating
Adjuster buckles	Zinc plated steel with EP coating
Chest connection	Zinc plated steel with EP coating
Leg connection	Zinc plated steel with EP coated buckle, stainless steel grommets
Pads	EVA and NBR foam, polyester
Lanyard keepers	Nylon
Belt	Polyester webbing, zinc plated steel with EP coated buckle, stainless steel grommets