



023-1334 through 023-1338

Pro-Shield Full Body Harness: 1D, DE MB Chest, TB Legs

FEATURES :

- Polyurethane coated webbing for water and chemical resistance (see back for more information)
- Dorsal D-ring
- Dielectric offset mating buckle chest
- Dielectric mating buckle torso adjusters
- Tongue buckle legs
- Easy to clean with increased durability

FALL ARREST POINT(S) :

- 1 Dorsal D-ring

ITEM WEIGHT :

- 4.4 lbs. (2.0 kg)



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.11-2021
OSHA	1926.502, 1910.140

SIZE(S)	
023-1334	X-Small
023-1335	Small / Medium
023-1336	Large / X-Large
023-1337	2X
023-1338	3X

COMPONENT	MATERIAL SPECIFICATION
Webbing	Polyurethane coated polyester
D-ring	Zinc plated alloy steel
Adjuster buckles	Dielectric coated steel
Chest connection	Dielectric coated steel
Leg connection	Steel tongue buckle w/ SS grommets
Label Cover	Polyester



CHEMICAL RESISTANCE RATING

RATING SCALE	
EXCELLENT - Little or no change	5
GOOD - Slight loss in properties, slight swell	4
FAIR - Some loss in properties, swelling	3
POOR - Significant loss of properties, significant swelling	2
DISSOLVES - Not recommended	1

ACIDS	RATING	ORGANICS (CONT.)	RATING
ACETIC, 5%	4	DIOCTYL PHTHALATE	3
FORMIC, 20%	2	ETHYL ETHER	3-4
HYDROCHLORIC, 10%	3	ETHYLENEN GLYCOL	4
OLEIC	3-4	ETHYLENEN GLYCOL, 50% H2O	4
SULFURIC, 20%	3	GASOLINE, 100 OCTANE	3
		HEXANE	3-4
ALCOHOLS		KEROSENE	4
ETHANOL	2	METHYLENE CHLORIDE	2
ISOPROPANOL	2-3	METHYL ETHYL KETONE	2
ISOPROPANOL, 50%	2-3	N-NETHYL-2-PYRROLIDENE	1
METHANOL	2	OIL, TEXAS CRUDE	3-4
		OIL, DETERGENT 20W	4
ALKALI		OIL, NONDETERGENT 20W	4
SODIUM HYDROXIDE, 20%	3	OIL, SKYDROL TYPE B	1
		OIL, SKYDROL TYPE 500A	2-3
ORGANICS		OIL, SKYDROL TYPE 500B	2-3
ACETONE	2	OIL, TRANSMISSION TYPE A	4
ASTM FUEL A	4	PERCHLOROETHYLENE	2
ASTM FUEL B	3	PYRIDINE	1
ASTM FUEL C	2-3	TETRAHYDROFURAN	1
ASTM OIL #1	4	TOLUENE	2
ASTM OIL #2	4	TRICHLOROETHYLENE	2
ASTM OIL #3	3-4	TURPENTINE	4
BENZENE	2		
BRAKE FLUID, TYPE A	2	MISCELLANEOUS	
BRAKE FLUID, (H.D.)	3-4	CLOROX, 5%	4
		CALCIUM SOLUTION SATURATED SOLUTION	4
BUTANE	4	HYDROGEN DISULFIDE, 5%	5
CARBON TETRACHLORIDE	2	SODIUM CHLORIDE SATURATED SOLUTION	4
		SYNTHETIC PERSPIRATION	4
CYCLOHEXANONE	1	TIDE DETERGENT, 1%	4
DIMETHYL FORMAMID	1	WATER	4
DIMETHYL SULFOXIDE	1		
1,4-DIOXANE	1		

IMPORTANT: These ratings are based on testing but should be considered a general guide for contact with these chemicals. Due to variances in jobsite conditions, methods and equipment used with these materials, Safewaze makes no guarantees or warranties on the suitability of this product for the user specific applications. Please follow proper product inspection guidelines and competent person judgement to ensure the safety of the user.