



023-5320

Lodestar 30' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength housing for durability
- Built-in handle for convenience
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- Optimized walking speeds to reduce nuisance lock-ups
- All components are Z359.12 compliant

Eligible for service and repair

Class
1
Anchor at or above dorsal D-ring



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 41 in. (104 cm)
Actual arrest distance	≤ 41 in. (104 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. 11 in. (2.1 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized or stainless steel (dependent on configuration)
Tagline	3mm polyester rope



023-5321

Lodestar 50' Cable SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion
- High strength housing for durability
- Built-in handle for convenience
- Braking system activates quickly to arrest fall
- Load indicating snap hook easily identifies when product has arrested a fall
- Optimized walking speeds to reduce nuisance lock-ups
- All components are Z359.12 compliant

Eligible for service and repair



Class
1
Anchor at or above dorsal D-ring

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 30 in. (76 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	6 ft. (1.8 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel
Cable	3/16" Galvanized or stainless steel (dependent on configuration)
Tagline	3mm polyester rope



023-5321

Lodestar 50' Cable SRL

LODESTAR

Standards: ANSI Z359.14-2021
 OSHA 1910.140, 1910.66 & 1926.502

Capacity: ANSI 130-310 lbs. (59-141 kg)
 OSHA Up to 420 lbs. (191kg)

CONNECTOR

ATTACHMENT

Part Number	Single Leg (S) / Dual Leg (D)	SRL Class	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	CONNECTOR										ATTACHMENT																								
								U-Steel Swivel Snap Hook	Steel Snap Hook	Dielectric Snap Hook	ALU Snap Hook	Steel Tie Back Hook	Steel Rear Hook	U-Steel Swivel Rear Hook	Steel Swivel Rear Hook	Steel Swivel Rear Hook	ALU Swivel Rear Hook	Steel Captive Eye Carabiner	ALU Swivel Carabiner	ALU Swivel Carabiner	No Attachment	Trip Lock Steel Carabiner	ALU Captive Eye Carabiner	ALU Carabiner	ALU Captive Eye Carabiner	ALU Snap Hook	FS-EX213	Cab Mount Bracket	Integrated B/W	Soft Loop	JD14 B/W	9012 B/W	9013 B/W									
023-5320	1	S	30	Steel Cable	Ø3/16	Nylon	13.4		X																X																	
023-5321	1	S	50	Steel Cable	Ø3/16	Nylon	16.4	X																		X																

