



Are SRL nuisance lockups getting in the way of performance?

The Lodestar SRL offers improved walking-working speeds to keep work on the jobsite moving.

LODESTAR CABLE SRL

EFFICIENT

Optimized walking speed reduces nuisance lock-ups

PRACTICAL

Built-in carry handle plus built for durability

MOBILE

Swivel attachment point for wide range of motion

Offered in both Class 1 and Class 2 models to give you exactly what you need for the job at hand.

CLASS

1

Anchor at or above dorsal D-ring

CLASS

2

Anchor above or below dorsal D-ring

Superior functionality with increased worker efficiency



SKU	CLASS	LENGTH
023-5320	1	30'
023-5321	1	50'
023-5325	2	30'
023-5326	2	50'

KEY SPECS:

Materials: Nylon and glass fiber housing, zinc plated steel carabiner and load indicating swivel snap hook, 3/16" galvanized steel cable, polyester rope tagline
ANSI Weight Capacity: 130-310 lbs. (59-141 kg)
OSHA Weight Capacity: Up to 420 lbs. (191 kg)
ANSI Standards: Z359.14-2021
OSHA Standards (Class 1): 1910.140, 1910.66, 1926.502
OSHA Standards (Class 2): 1910.140, 1910.66

