



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

FS-FSP15085-W-RBH-BWB 7' CLASS A Dual-Leg Web Retractable w/ In-Webbing Bracket and Rebar Hooks



Features and Benefits	Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The FS-FSP15075-W-RBH-BWB features a mobility-enhancing swivel-top, a rugged and durable housing, and a unique braking system that eases shock in the event of a fall. Fall indicator sewn into webbing.
Length of Web	7 ft (2.13 m)
Weight of Unit	9 lbs (4.08 kg)
Materials	Aluminum housing 1 in (25.4 mm) Ultrahigh Molecular Weight webbing w/ sewn-in fall indicator Forged steel rebar hooks Steel carabiner
Hook Ratings	5,000 lbs (2267.96 kg) Tensile Strength 3,600 lbs (1632 kg) Gate Rated
Arresting Force	Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)
Maximum Arrest Distance	<24 in (609.6 mm)
Maximum Working Load	ANSI 130-310 lbs (58.97-140.61 kg) OSHA up to 420 lbs (190.51 kg)
Webbing Tensile Strength	4,200 lbs (1905.09 kg)
Applicable Standards	Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32