



[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET

### 018-5027

7' Dual Leg Web Retractable w/  
Aluminum Locking Rebar Hooks and  
Behind the Web Bracket



<b>Features and Benefits</b>	Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The 018-5027 features unique clear plastic housings for enhanced unit inspections and a revolutionary internal braking system, which alleviates the need for an external shock pack in such a small, ergonomic SRL . Fall indicator is sewn into webbing.
<b>Length of Web</b>	7 ft (2.13 m)
<b>Weight of Unit</b>	5.8 lbs (2.63 kg)
<b>Materials</b>	High-strength clear plastic housings .77 in (19.5 mm) Ultrahigh Molecular Weight Webbing Aluminum rebar hooks Aluminum and Forged steel Behind the Web Bracket
<b>Hook Ratings</b>	5,000 lbs (2267.96 kg) Tensile Strength 3,600 lbs (1632 kg) Gate Rated
<b>Maximum Arresting Force</b>	<1,800 lbs (816.47 kg)
<b>Maximum Arrest Distance</b>	Class A up to 24 in (60.96 cm) if used above Dorsal D-ring Class B up to 54 in (137.16 cm) if used up to a maximum of 2 ft below Dorsal D-ring
<b>Maximum Working Load</b>	ANSI 130-310 lbs (58.97-140.61 kg) OSHA up to 420 lbs (190.51 kg)
<b>Webbing Tensile Strength</b>	4,200 lbs (1905.09 kg)
<b>Applicable Standards</b>	Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32