## SAFEWAZE TM <u>safewaze.com</u> | (P) 704-262-7893 | (F) 704-262-9051 322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET



## **FS-EX213**

Hybrid Mega Swivel 10K Anchor

**Description** Fall Protection removable / reusable Hybrid Mega Swivel anchor.

Easy installation and removal. Must follow installation instructions for proper installation. Can be used in horizontal, vertical and overhead

applications.

**Length** 6.25 in (158.75 mm)

Diameter 1 in (25.4 mm)

Materials Return Wire - Aircraft Cable

Cone, Spoons - Stainless Steel

Retaining Bushing, Bolt, Sleeve, Swivel - Zinc Plated Steel

Compression Bushing - Polyethylene

Minimum Tensile Strength 10,000 lbs - 44 kN

Weight 2.10 lbs (952.5 g)

Weight Capacity 310 lbs (140.61 kg) - Single user

Applicable Standards Meets OSHA 1926.502 - OSHA 1910.66 - ANSI Z359.1

ANSI Z359.7

<sup>\*</sup>Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.2kN) pounds per employee attached.