SAFEWAZE TM <u>safewaze.com</u> | (P) 704-262-7893 | (F) 704-262-9051 322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET



FS-EX237

Hybrid Mega Swivel 10K Mining Anchor 39 mm (Fall Protection)

Description Fall Protection removable / reusable Hybrid Mega Swivel Mining

anchor. Easy installation and removal. Must follow installation instructions for proper installation. Can be used in horizontal, vertical

and overhead applications.

Length 11.5 in (293 mm)

Diameter 1.5 in (39 mm)

Materials Return Wire - Aircraft Cable

Cone, Spoons - Stainless Steel

Retaining Bushing, Bolt, Sleeve, Swivel - Zinc Plated Steel

Compression Bushing - Polyethylene

Minimum Tensile Strength 10,000 lbs - 44 kN

Weight 2.4 lbs (949 g)

Weight Capacity 310 lbs (140.61 kg) - Single user

Applicable Standards Meets OSHA 1926.502 - OSHA 1910.66 - ANSI Z359.1

ANSI Z359.7

^{*}Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.2kN) pounds per employee attached.