



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

SAFEWAZE SAFELINK™

FS-EX2505 SafeLink SafetyLink Adjustable Safety Strap



Description SafeLink SafetyLink Adjustable Safety Strap for use with the SafeLink Horizontal Lifeline System. Provides backup safety point for the FS-EX2510 Come-A-Long. Installs in parallel with the Come-A-Long, connecting to the anchor point and cable lifeline
See SafeLink User Manual for installation instructions.
****Visually Inspect The Unit Before Installation****

Attachment Point 2 Double-locking snap hooks

Materials 1 in Polyester webbing: Breaking strength > 5,000 lbs
High-Strength polyester stitching: Breaking strength > 40 lbs
Forged steel snap hooks: Break load: 5,000 lbs. Gate rated at 3,600 lbs
Wear Sleeves at ends

Weight 2 lbs (0.91 kg)

Length Adjustable to 4 ft (1.22 m)

Minimum Working Load 310 lbs (140.61 kg) per person; Up to 4-person SafeLink System

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.1 - ANSI A10.32