



SAFEWAZE™
 safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
 322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET



FS-EX326 18" Anchor Point Post (For Wood, Steel, and Concrete)

Description	Safewaze™ FS-EX326 18" Anchor Point Post is easy to install. Any attachment material must be rated to meet OSHA, federal, state, and local government regulations for fall protection anchor points.
Dimensions	16 in X 16 in (406.4 mm x 406.4 mm) Baseplate 20" (508 mm) Overall height from bottom of baseplate to top of loop
Number of Holes in Base	(40) - Fasten with #14-10 2" wood screws (Not Included). Screws must extend through deck 3/4" minimum (40) - Fasten with #14-14 2" screws for metal decking (Not Included). Screws must penetrate metal decking by at least 1/4" (8) - Fasten with 1/2" Hilit HIT-Z Rods or equivalent (Not Included). Minimum 3-1/2" embedment required
Deck Requirements	Minimum 5/8" CDX Plywood. All screw holes must be used. Minimum 20 gauge steel material for steel installation. All screw holes must be used. Minimum 6" thick, 2,500 p.s.i., concrete for concrete installation. All concrete fastener installation holes must be used.
Material	Galvanized Steel
Working Load	310 lbs (140.61 kg) - Designed for single person use
Strength	5,000 lbs (2267.96 kg) Ultimate Strength. Supporting structure must have a strength of at least 5,000 lbs (2267.96 kg)
Weight	36 lbs (16.33 kg)
Applicable Standards	Meets OSHA 1926.502 - ANSI Z359.1 - ANSI A10.32

***Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.2kN) pounds per employee attached.**