




safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
 322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

SAFEWAZE SAFELINK™

FS-EX5501-5 SafeLink Post Anchor



Description Aluminum Post designed for use with the SafeLink Horizontal Lifeline System. Each post has two (2) sets of 9/16 in (14.29 mm) holes set 4 in (101.60 mm) apart and at 90° for the FS-EX2508 eye-bolts (not included). When SafeLink Horizontal Lifeline System spans exceed 65 ft (19.81 m), or when a span needs to be reduced to accommodate low clear-story height work, the use of an intermediate anchorage post (FS-EX2517) should be considered.

See SafeLink User Manual for installation instructions.

****Visually Inspect The Unit Before Installation****

Wall Thickness 1/2 in (12.7 mm)

Outside Diameter 3-1/2 in (88.9 mm)

Length 7-1/2 ft (2.29 m)

Weight 40.5 lbs (18.37 kg)

Material 6061-T6511 Aluminum

Minimum Tensile Strength 5,000 lbs (2267.96 kg)

Maximum Working Load 310 lbs (140.61 kg) per person; Up to 4-person SafeLink System

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.1 - ANSI A10.32