



[safewaze.com](http://safewaze.com) | (P) 704-262-7893 | (F) 704-262-9051  
322 Industrial Court, Concord, NC 28025

## TECHNICAL DATA SHEET

### FS595

6' Stretch Low-Profile Shock Lanyard  
w/ Rebar Hook



|                              |  |
|------------------------------|--|
| <b>Features and Benefits</b> | Fall arrest lanyard with one rebar hook (connects to anchor point) and one snap hook (connects to harness D-ring). Elastic webbing allows for maneuverability. Rebar hook designed to fit Symons Form. |
| <b>Length</b>                | 4 ft (1.22 m) to 6 ft (1.83 m)   |
| <b>Weight</b>                | 3.4 lbs (1.54 kg)  |
| <b>Weight Capacity</b>       | 310 lbs (140.61 kg)  |
| <b>Attachment Point(s)</b>   | 1 Snap hook - 1 Rebar hook   |
| <b>Materials</b>             | 1-3/8" (34.93 mm) Stretch Tubular Web<br>High-strength polyester stitching<br>Forged steel snap hook and rebar hook, each:<br>3,600 lbs Gate-rated; Min breaking strength > 5,000 lbs                  |
| <b>Applicable Standards</b>  | Meets OSHA 1926.502 - ANSI Z359.13 - ANSI A10.32   |