



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET



FS861

Sliding Beam Anchor

Description	The Safewaze™ sliding beam anchor is designed to be used as a single-person anchor point on horizontal beams, and features a patented one-handed double-action latch system, ergonomic finger grips, and centered D-ring that prevents jamming and allows for smoother sliding on beam flanges.
Length	18.5 in (469.9 mm)
Weight	3.5 lbs (1.58 kg)
Fits Beam Flange Width	3.5 in (88.9 mm) to 12 in (304.8 mm)
Fits Beam Flange Thickness	.25 in (6.35 mm) to 1.25 in (31.75 mm)
Weight Capacity	310 lbs (140.61 kg)
Materials	Aluminum: Cross Bar, Clamps Bronze: Flange Insert Stainless Steel: D-ring Bracket Zinc Plated Steel: D-ring, Spring, Hardware
Minimum Breaking Load	5,000 lbs (2267.96 kg)
Applicable Standards	Meets OSHA 1926.502 - ANSI Z359.1 - ANSI A10.32

*Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.2kN) pounds per employee attached.