



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

FS871

Knock-Down Roof Anchor



Description	The Safewaze™ knock-down roof anchor is designed to be used as a single anchor point for no more than one person at a time. Connection to anchor must be made with locking carabiner or double-locking snap hook. Attach anchor with (8) 16-penny spiral nails (3 in min length). All holes must be used in anchorage.
Length	16.25 in (7.37 mm)
Weight	0.79 lbs (0.36 kg)
Material	Galvanized sheet steel
Material Thickness	0.06 in (1.52 mm)
Distance (from bottom to top holes)	4.44 in (112.78 mm)
Width of Plate	1.75 in (44.45 mm)
Number of Holes	8
Hole Diameter	0.18 in (4.57 mm)
Weight Capacity	310 lbs (140.61 kg)
Minimum Breaking Load	5000 lbs (2267.96 kg)
Applicable Standards	Meets OSHA 1926.502 - ANSI Z359.1 - ANSI A10.32

***Anchorages used for attachment of personal fall arrest equipment shall be independent of any anchorage being used to support or suspend platforms and be capable of supporting at least 5,000 (22.2kN) pounds per employee attached.**