

### FS77125-UT-QC Dielectric Arc Flash Harness



|                              |   |
|------------------------------|---|
| <b>Features and Benefits</b> | ASTM F887 electric arc performance and 35KV ASTM dielectric rating<br>No-tangle D-ring pad reduces web knotting and relieves D-ring back pressure<br>New technologically advanced front D-ring design<br>Reinforced web loop front rescue ring attachment |
| <b>Attachment Point(s)</b>   | 1 Dorsal D-ring and 1 Web loop Front rescue D-ring  |
| <b>Materials</b>             | 1.75 in (44.45 mm) Nylon webbing<br>High-strength polyester stitching<br>No-tangle D-ring back pad<br>Dielectric Dorsal D-ring<br>Front web loop rescue ring<br>Aluminum Quick connect leg buckles with leather shield pads at legs                       |
| <b>Weight</b>                | 3.5 lbs (1.59 kg)   |
| <b>Weight Capacity</b>       | 310 lbs (140.61 kg)   |
| <b>Sizes</b>                 | S - M - L - XL - XXL  |
| <b>Applicable Standards</b>  | Meets OSHA 1926.97 - OSHA 1910.269 - OSHA 1926.502<br>ANSI A10.32 - ANSI Z359.1<br>ASTM F887-13 (40 CAL/CM SQUARED)   |